

# 5CG8

## Medium-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CG8 is the same as the 6CG8A except for the following items:*

Heater, for Unipotential Cathode:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CL8A

## Medium-Mu Triode— Sharp-Cutoff Tetrode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CL8A is the same as the 6CL8A except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp

# 5CM8

## High-Mu Triode— Sharp-Cutoff Pentode

9-PIN MINIATURE TYPE

With Heater Having Controlled Warm-Up Time

*The 5CM8 is the same as the 6CM8 except for the following items:*

Heater, for Unipotential Cathodes:

Voltage (AC or DC) . . . . .	4.7	volts
Current . . . . .	0.6 ± 6%	amp



RADIO CORPORATION OF AMERICA  
Electron Tube Division  
Harrison, N. J.

DATA  
7-61